

10/529300

JC17 Rec'd PCT/PTO 25 MAR 2005

IN THE CLAIMS:

Please amend the claims as shown below, in which deleted terms are shown with strikethrough and/or double brackets, and added terms are shown with underscoring. This listing of the claims will replace all prior versions, and listings, of claims in the application.

Claim 1 (currently amended). An electronic key system for a vehicle ~~which includes, the~~ electronic key system comprising a control apparatus (14) mounted on ~~an actual~~ the vehicle (100A) and an electronic key (12), wherein

the control apparatus includes a transmitting antenna,

the electronic key permits for transmitting transmission of a response signal (Sa) in response to receiving of a request signal (Sr) transmitted from said control apparatus (14) through a ~~the~~ transmitting antenna (72), characterized in that and

said transmitting antenna (72) is installed in the proximity of the center of said ~~actual~~ vehicle (100A).

Claim 2 (currently amended). An electronic key system for a vehicle according to claim 1, characterized in that wherein

said transmitting antenna (72) is installed at a position within a range from an upper portion of the vehicle to a lower portion of the vehicle, and within a range from a point at one fourth of a wheel base to another point at three fourths of a the wheel base (154) with reference to the center (150a) of a front wheel (150) of said ~~actual~~ vehicle (100A).

Claim 3 (currently amended). An electronic key system for a vehicle according to claim 1,

characterized in that wherein

where said ~~actual~~ vehicle (100A) includes a seat (140) on which a user is to be seated, said transmitting antenna (72) is installed in the proximity of a front portion of said seat (140).

Claim 4 (currently amended). An electronic key system for a vehicle ~~which~~ includes a control apparatus (14) mounted on ~~an actual~~ the vehicle (100B) and an electronic key (12), wherein

the control apparatus comprises a transmitting antenna,
the electronic key permits transmission of for transmitting a response signal (Sa) in response to receiving of a request signal (Sr) transmitted from said control apparatus (14) through ~~a~~ the transmitting antenna (72), characterized in that

~~said actual vehicle (100B) includes a seat (140) provided for~~ which permits opening and closing movement ~~for being seated by a user~~ and a locking apparatus (64) for locking said seat (140) ~~so as not to be opened to prevent opening of the seat until a~~ unlocking instruction is supplied thereto; ~~that~~

said control apparatus (14) includes ~~means for verifying a verifier which verifies~~ the response signal (Sa) and a driver which outputs outputting an unlocking instruction to said locking apparatus (64) when it is discriminated that the response signal (Sa) is a request from a legal user; and ~~that~~

said transmitting antenna (72) is installed on said seat (140) or in the proximity of said seat (140).

Claim 5 (currently amended). An electronic key system for a vehicle according to claim 4, characterized in that wherein said transmitting antenna (72) is provided on a left side face of said seat (140).

Claim 6 (currently amended). An electronic key system for a vehicle according to claim 4,
characterized in that wherein

~~where at least the vehicle comprises~~ a seat handle (144) which is used to manually open or close said seat (140) ~~by manual operation, and~~ is provided around a rear portion of said seat (140), and said transmitting antenna (72) is installed on said seat handle (144).

Claim 7 (new). An electronic key system for a vehicle, the electronic key system comprising a control apparatus mounted on the vehicle and an electronic key, wherein

the control apparatus includes a transmitting antenna,
the electronic key permits transmission of a response signal in response to receiving a request signal transmitted from said control apparatus through the transmitting antenna, and
said transmitting antenna is installed on the vehicle in a location which provides a transmission range which includes at least a space occupied by a vehicle operator during vehicle use.

Claim 8 (new). The electronic key system for a vehicle of claim 7 wherein the transmitting antenna is installed on the vehicle in a location which provides a transmission range including the entire vehicle.

Claim 9 (new). The electronic key system for a vehicle of claim 7 wherein initiation of operation of the vehicle is permitted only when the electronic key is within the transmission range, and wherein a warning is provided when the electronic key is moved out of the transmission range during operation of the vehicle.

Claim 10 (new). The electronic key system for a vehicle of claim 7 wherein the control apparatus and the electronic key communicate at regular intervals during operation of the vehicle.

Claim 11 (new). The electronic key system for a vehicle of claim 10 wherein a warning is issued by the control apparatus if communication between the control apparatus and the electronic key fails for a predetermined length of time.

Claim 12 (new). The electronic key system for a vehicle of claim 1 wherein said transmitting antenna is installed on the vehicle in a location which provides a transmission range including at least a space occupied by a vehicle operator during vehicle use.

Claim 13 (new). The electronic key system for a vehicle of claim 1 wherein said transmitting antenna is installed on the vehicle in a location which provides a transmission range including at least a space occupied by a vehicle operator during vehicle use, initiation of operation of the vehicle is permitted only when the electronic key is within the transmission range, and a warning is provided when the electronic key is moved out of the transmission range during operation.

Claim 14 (new). The electronic key system for a vehicle of claim 1 wherein the control apparatus and the electronic key communicate at regular intervals during operation of the vehicle.

Claim 15 (new). The electronic key system for a vehicle of claim 14 wherein a warning is issued by the control apparatus if communication between the control apparatus and the electronic key fails for a predetermined length of time.

IN THE ABSTRACT:

Please amend the abstract as shown below, in which deleted terms are shown with strikethrough and/or double brackets, and added terms are shown with underscoring

ABSTRACT

A vehicle-use electronic key system ~~comprising~~ includes a control unit [(14)] mounted on a real car [(100A)], and an electronic key [(12)] for sending a response signal [(Sa)] on receiving a request signal [(Sr)] sent from the control unit [(14)] via a transmission antenna [(72)], the antenna [(72)] being installed near the middle of the real car [(100A)]. Specifically, when a line segment (wheel base) [(154)] connecting the center [(150a)] of a front wheel [(150)] to the center [(152a)] of a rear wheel [(152)] is assumed, the transmission antenna [(72)] is installed in any location within a range from the upper part to the lower part of the real car [(100A)] within a range from a 1/4 point [(P1)] to a 3/4 point [(P2)] of the wheel base [(154)] with the center [(150a)] of the front wheel [(150)] as a reference.